Chapter 4 – Introduction to the C language

The C language was created in the 1970s by Dennis Ritchie and Brian Kernighan, and was instrumental in the development of the Unix operating system. The language was made very popular in part thanks to a "tutorial" book by the two designers, simply titled *The C Programming Language*. This book remains relevant to this day, and we will be relying heavily on references to it in this course.

Exercise 1 Search the web for an electronic copy of the K&R in a format that you like (html, epub, pdf...), maybe translated in your native tongue. Warning: we want the second edition from 1988, not the original from 1973. For instance, you can use this one:
`https://archive.org/details/the-c-programming-language-second-edition-first-190-pages/`

1 Basic Syntax

A C program is a collection of **functions** which call each other. One of these functions must be named `main()`, so that the operating system (Linux, in our case) knows where execution should start.

Exercise 2 Create a file named `hello.c` and type in the program below. Compile it into an **executable** file with command `gcc -g -Wall -Wextra -Werror -o hello hello.c`, then run it with `./hello`. Ask us questions about anything mysterious. From here on, be sure to always always always use these same three `-W...` options to compile your code, they will save you from a lot of hard-to-find bugs.
Most exercises in this chapter ask you to write programs. Always create a new source file for each exercise, because you may have have to retrieve an old file at some point.
Also: **please do take notes** about what you're learning along the way, otherwise you will forget most of it before the exam.

```c
#include <stdio.h>

void print_hello() {
    printf("Hello, world\n");
}

int main() {
    print_hello();
    return 0;
}
```

The `printf()` function (provided by library `stdio.h`) is useful to display text on screen but it can also be invoked with several arguments, in which case it will perform **data formatting**. The first argument, the so-called *format string* is searched for percent signs, which will then be interpreted as *format codes*. Each **printf format code** describes how one of the subsequent arguments should be displayed. For instance, `printf("%d vs %x vs %c\n",42,42,42)` prints the same value three times: as a number written in decimal, in hexadecimal, and as as an ASCII character. Try it out !

Exercise 3 Type the program below in a file named `formatting.c`, then compile and execute it. Read the docs (K&R §7.2 and/or link below) and ask us questions until you are able to explain what each line of ths program does. Do take notes about what you learn (10 cases in total).
`https://www.gnu.org/software/libc/manual/html_node/Table-of-Output-Conversions.html`

```
#include <stdio.h>

int main() {
    printf("0. %c \n", 'a');
    printf("1. %c \n", 65);
    printf("2. %d \n", 100);
    printf("3. %x \n", 100);
    printf("4. %o \n", 100);
    printf("5. %#x \n", 100);
    printf("6. %#o \n", 100);
    printf("7. %6.2f \n", 3.1416);
    printf("8. %6.2f \n", 31.416);
    printf("9. %E \n", 3.1416);
    printf("10. %*d \n", 5, 10);
    return 0;
}
```

Exercise 4 Write a program that prints the number -1 but in hexadecimal notation. What does it show on screen ? Give a one sentence explanation of why this is the case.

2 Variables

A **variable** is a symbolic (i.e. plain-text) name which identifies a memory location. The C language offers two kinds of variables: **global variables** which are visible from everywhere, and **local variables** which belong to one particular function. Each variable has a fixed **data type**:

- `int` for whole numbers aka **integers**, such as $0, 1, 2$ or -42,
- `float` for numbers with a decimal point aka **floating-point numbers**, like 3.14 or -5.3
- `char` for one-byte integer values (typically, ASCII-encoded **characters**).

Exercise 5 Read K&R §2.2 and §2.4 to learn more about types and variable declaration, then answer the questions below:

- What is the range of values that can be stored in a signed `char` variable ?
- How do you declare a constant (aka read-only variable) named `pi` with value 3.14 ?

Variables can be **assigned** a new value using the "equals" sign, e.g. `x = 36;` or `y = x+10;` The job of the compiler is to translate such a statement into a sequence of machine instructions which:

1. evaluate the expression on the right-hand side, and then
2. store the result in memory at the correct address.

Warning: **expressions** are always evaluated with the same type as their operands. For instance, `5/10` is an integer division and evaluates to zero, but `5.0/10.0` evaluates to `0.5`. Try variations around this idea: start with `printf("%d %g\n",5/10,5./10.);` then play with different combinations of floats and ints.

Exercise 6 Write a program which initializes two integer variables with positive values, computes their ratio as a `float` and then shows it as a percentage[1] For instance with `int a=3;` and `int b=9;` your program should print something like *3/9=33.33%*

Each function can also send a **return value** to its caller using the "return" keyword, e.g. `return 42;` or `return x+y;` Functions that return nothing, like `print_hello()` on on the preceding page, must declare their **return type** as being `void` and must use the `return;` keyword with no operand. Functions that do return a value must have a unique, well-defined return type.

[1] To find out how to get `printf()` to show a literal percent sign, refer to K&R §7.2

3 Control Structures

Conditional statements are based upon the "if" and "switch" keywords, as illustrated below:

```
if( condition )
{
  ... // then do something
}
// in both cases,
// execute here afterwards
```

```
if( condition )
{
  ... // then do something
}
else
{
  ... // do something else
}
// in both cases,
// execute here afterwards
```

```
switch( integer expr )
{
    case 42:
    ...
    break;

    case -5:
    ...
    break;

    default:
    ...
    break;
}
// 'break' jumps here
```

Exercise 7 Many data types are implemented as integers. For instance, there are no proper **booleans**: value zero means "false" and any non-zero value means "true". Even comparison operators like "==" or "<" actually produce an integer. For this reason, `if(x != 0)` and `if(x)` are equivalent. Read K&R §2.6, ask us about anything confusing, then answer the questions below:

- How do you write "*if(x>0 and x<10) then ...*" in C ?
- How can you *negate* a logical condition, i.e. "*if(not condition) then ...* "?

Exercise 8 Within a `switch-case` construct, be sure to always add a `break` statement at the end of every branch, otherwise control will **fall through** to the next branch which is perfectly allowed but rarely what you wanted. Read K&R §3.4 until `switch-case` feels familiar, ask us about anything confusing, then answer the questions below:

- What happens if the programmer does not include a `default` branch ?
- How do you you write a `switch-case` for non-integer types like `float` ?

There are several **loop constructs** in C, which behave as repeated "if" statements (cf K&R §3.5).

```
while( expr )
{
   body;
}
```

$\sim$

```
label:
if( expr )
{
  body;
  goto label;
}
```

```
for( code1; expr; code2 )
{
   body;
}
```

$\sim$

```
code1;
while( expr )
{
  body;
  code2;
}
```

Remarks (cf K&R §3.7):

- The `continue` keyword skips the remainder of the loop body and jumps directly to the next iteration.
- The `break` keyword exits the current innermost loop (or switch-case) entirely.

Exercise 9 Write three programs which print numbers from 1 to 10 using a `for` loop, a `while` loop, and a `do-while` loop respectively.

4 Functions

For the compiler to generate correct machine instructions when calling a function, it must know the data type of every argument (and return value), collectively known as the **function's signature**. For historical reasons, this information must come *before* (in line number order, in the source file) the place where the function is invoked. If the entire **function definition** comes before the first call site, like illustrated by our `print_hello()` on page 1, then everything is fine. Otherwise, the programmer must first write a **function declaration** to provide the signature, as illustrated below:

```c
#include <stdio.h>

void print_hello() ;

int main() {
    print_hello();
    return 0;
}

void print_hello() {
    printf("Hello, world\n");
}
```

Exercise 10 Open file `/usr/include/stdio.h` and find where `printf()` is declared. (You don't need to understand all the syntax details)

Exercise 11 Implement a **recursive function** with signature `int fib(int n)` which computes the nth Fibonacci number: fib(0) = 0, fib(1) = 1, otherwise fib(n) = fib($n-1$) + fib($n-2$).
In your `main()` function, invoke `fib()` in a `for` loop to print the first 20 Fibonacci numbers.

Exercise 12 In another source file, implement an **iterative** (i.e. non-recursive) version of `fib()`, with the same signature. You can reuse your `main()` function to check that both implementations produce the same results.

Exercise 13 Write a program which loops over every number k from 1 to 50 and:

- when k is a multiple of 3, print "*IST*",
- when k is a multiple of 5, print "*OPS*",
- when k is both a multiple of 3 and 5, print both "*IST*" and "*OPS*",
- otherwise just print k.

The expected output is illustrated on the right.

```
1
2
IST
4
OPS
IST
7
8
IST
OPS
11
IST
13
14
IST OPS
16
17
...
```

To find out if `x` is a multiple of `y`, you can use the percent sign operator to perform a **modulo** operation (aka remainder of the integer division) with e.g. `if(x%y == 0)`

Exercise 14 Implement a function with signature `void tree(int R)`, which draws a pine tree with `R` horizontal rows of "leaves" and a 3x2 centered "trunk", as illustrated below.

R=2

```
 *
***
|||
|||
```

R=6

```
     *
    ***
   *****
  *******
 *********
***********
    |||
    |||
```

R=13

```
             *
            ***
           *****
          *******
         *********
        ***********
       *************
      ***************
     *****************
    *******************
   *********************
  ***********************
*************************
            |||
            |||
```